

# HOT STAIN REMOVER

## ALKALINE MASONRY CLEANER

### DESCRIPTION AND USE

Hot Stain Remover is a high pH alkaline cleaning product that will remove both food and petroleum oil staining and remove heavy carbon deposits and oil from metal, wood or masonry. Hot Stain Remover undiluted may strip latex and enamel paints.

### ADVANTAGES

- \* Removes heavy carbon deposits
- \* Removes both food and petroleum oil staining

### LIMITATIONS

- \* Will etch windows

### TECHNICAL DATA

Appearance & Odor: Amber color, mild citric odor  
Physical State: Liquid  
pH: 13.5  
Vapor Pressure (mmHg): As water  
Vapor Density (air=1): As water  
Boiling Point: 210°F  
Freezing/Melting Point: N.A.  
Specific Gravity (water =1): 1.12  
Evaporation Rate: As water  
Solubility in water: Complete.

### PREPARATION

Protect anodized aluminum, glass and painted substrates. Cover foliage with polyethylene or other proven protective material. Avoid wind drift on surrounding surfaces such as auto and pedestrian traffic.

### SURFACE & AIR TEMPERATURES

Excessively high or low temperatures will produce poor results and possible harm. Best cleaning results are obtained when air and surface temperatures are 40° Fahrenheit or above. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for surface to thaw. If air temperatures exceed 90° Fahrenheit, flash cool the surface with water before applying product. Do not allow products to dry on the surface. Always rinse thoroughly while still wet.

### PRE-TESTING

Always test prior to beginning full-scale cleaning operations. Testing should confirm cleaning effectiveness on each type of surface and stain designated to be cleaned. Test also to determine the desired surface contact time and any potential for adverse reactions with adjacent materials. Allow test

and results. Great care must be taken when applying this product because of its highly active penetrating nature.

### DILUTION

- Use undiluted for difficult removal up to 10:1 for brushing application

### SUITABLE SUBSTRATES

Metals, masonry materials, and wood

### APPLICATION INSTRUCTIONS

Always protect the surrounding area by covering with plastic. If you are spraying this product always try to stay away from or above the mist, as it will burn your skin. Pre-wet (do not soak), the area with water before applying the product. With a strong dilution, apply with a low pressure applicator. With a weaker dilution, apply with a downstream through a pressure washer at low pressure. A nylon brush can be used to apply, when necessary. Let the product dwell for fifteen minutes to an hour, depending on the severity. Hot Stain Remover has special additives that causes soils to rise to the surface. Craftsmanship determines the appropriate pressures for rinsing. A thorough rinse job is always recommended, however, our chemistry never requires flooding a wall. Pressures that mark or damage the surface should be avoided. When in doubt, follow the manufacturers recommended P.S.I. for the substrate.

### SAFETY INFORMATION

Precautionary Measures: Always wear goggles and rubber gloves when handling this product. Keep off of skin and clothing. If material comes in contact with clothing, wash before reuse. The product contains Potassium Hydroxide and Ethanol. Do not get in eyes, on skin or clothing. Avoid breathing vapors. Keep container closed when not in use. Use with adequate ventilation. Applicators should wear boots, gloves, face shields, and/or goggles to avoid splash to bare skin and eyes. Dispose of empty containers according to federal, state, and local requirements. Avoid drifting of material or rinse water onto autos and pedestrians by protecting or diverting such traffic. Do not dilute Hot Stain Remover with any product except water. Do not use for any other applications other than specified. Do not remove label. Read Material Safety Data Sheet for additional safety and health hazard information prior to use.



# HOT STAIN REMOVER

PRODUCT SPECIFICATION  
HOT STAIN REMOVER

## ALKALINE MASONRY CLEANER

### INSTRUCTIONS IN CASE OF CONTACT OR EXPOSURE

Eyes: Flush thoroughly with water for fifteen minutes. If irritation persists seek medical attention.

Skin: Wash off immediately with soap and water. If irritation persists, seek medical attention.

Ingestion: Do not induce vomiting. Drink large amounts of water. Seek medical attention.

Inhalation: Remove to fresh air. If irritation persists, call physician.

### NOTICE

This product has been classified in accordance with the hazard criteria of the CFR.

### DISCLAIMER

The information herein is given in good faith, but no warranty, either expressed or implied, is made. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot be sure or guarantee these are the only hazards which exist.

### CUSTOMER SERVICE

Factory personnel are available for assistance at 800-313-8505 and will send you additional information on products as necessary.

